



Dimensions	Height – 936mm	Width – 1351mm	Depth – 232mm
ENCLOSURE OPTIONS	Base/Indoor	Outdoor <i>Standard</i>	Outdoor <i>Cold Climate</i>
Product Code	PDS-52-W-L-(T*)-B	PDS-52-W-L-(T*)-S	PDS-52-W-L-(T*)-H
Temperature Range	(0°C - +34°C)	(-5°C - +34°C)	(-30°C - +34°C)
NEMA Protection Rating	NEMA3	NEMA4	NEMA4
Window Type		Anti-Reflective Polycarbonate	Anti-Reflective Glass
Universal Mounting Screen (Internal)	✓	✓	✓
Dual Security Locks	✓	✓	✓
Air Curtain TM (Pat.Pend)		✓	✓
Surge Protected Power	✓	✓	✓
Exterior Plenum Chamber Cooling		✓	✓
Internal Heater (Thermally Controlled)		✓	✓
Filter Cooling System		✓	✓
Enclosure Mounting	Flat Wall Brackets	Flat Wall Brackets	Flat Wall Brackets

Overview

Protecting against vandalism and aggressive weather conditions, the PDS-52 Landscape is a wall mounted outdoor enclosure, manufactured from rugged mild steel and sealed to NEMA3/4, creating a secure environment for an LCD display.









An attractive but modest design, the professional image of the PDS enclosure works well in an outdoor location, giving you a secure and wider channel to successfully deliver digital signage.

All Prices are ex-vat and Delivery



Armagard Hardware

T* - Territory Specific

- 
The Air Curtain TM - Directing a constant flow of air across an installed display, the Armagard Air-Curtain reduces damage from heat build, direct sunlight and freezing conditions, optimising the window for clarity, promotion efficiency and increasing display lifespan.
- 
Internal Heating – Stops your screen from freezing over in winter, Internal Heaters maintain the optimum level of warmth within the enclosure, increasing the average air temperature to sustain display longevity.
- 
Interior Mounting Brackets – Reducing twisting and distributing weight evenly, Armagard bracket arms can be moved independently forward or backwards, allowing installers to optimise their display for the best possible viewing angle.
- 
Dual Security Locks – Fitted with two key security locks, locking bar and anti-torsion bolts, Armagard placement security offers piece-of-mind for units left in unmanned locations.
- 
Anti-Reflective – Available in either glass or polycarbonate, anti-reflective windows reduce glare and surrounding light reflections, presenting a clear and accurate image when in direct sunlight. *(Note: Glare can never be fully removed, to reduce glare to its lowest level, we recommend an anti-reflective glass with a 1% reflection rating, over a polycarbonate of 8%)*
- 
Toughened Windows – Available in glass or polycarbonate, Armagard toughened windows carry unique high-strength properties, making them ideal for busy or vandal prone areas.
- 
Closed Cell Insulation – Improving thermal performance, Armagard's 25mm low temperature insulation eliminates any thermal bridges and improves energy efficiency throughout the enclosure.
- 
Plenum Chambers – Allows the enclosure to be fully jet washed while allowing a filtered air-flow to transfer heat away, Plenum Chambers prevent any water from entering the unit and damaging the display.